



Heavy Industrial Labelling™ range

Identification solutions for raw material processors

Applying tracking information onto raw materials such as metals, timber, stones and other building materials can be done in many ways - including the use of hanging tags and adhesive labels. Some materials can be hot at the point when they need to be labelled, while others can be rough, dusty or oily. Conventional solutions include handwriting, riveting or welding plates onto parts.

The Avery Dennison Heavy Industrial Labelling range allows label converters to offer a highly effective alternative labelling solution. It ensures traceability throughout the manufacturing process. Materials for conversion into both hanging tags and adhesive labels are available, covering different temperature ranges.

Labels and hanging tags applied at ambient temperatures can use cost effective solutions based on polyolefines. For peak temperatures up to +220°C, Avery Dennison offers heat stable polyester films. Topcoated aluminium films, featuring high abrasion and solvent resistance for thermal transfer print, can be used at temperatures up to +500°C.

KEY FEATURES

- > Productive labelling technology for raw material processors
- > Performs in extreme conditions
- > Bar codes can be applied very soon in the value chain
- > Eliminates manual marking of parts, automating track-and-trace
- > Tracks and traces inventory from initial manufacture to final delivery
- > Helps reduce material reworking costs
- > Complete portfolio covering a wide range of applications

APPLICATION AREAS

- > Metal processing
- > Building material industry
- > Timber industry
- > Manufacturing



| Product Code | Product Description | Max. Peak Temp | MOQ (SQM) | Service (EX WORKS) |
|--------------|---|----------------|-----------|--------------------|
| BJ213 | TRANSFER HDPE 95 MATT WH-S8094-SGP-BG45WH | +60°C | 1000 | CTO |
| BJ237 | HDPE TAG 190 MATT WHITE | +80°C | 1000 | FTO |
| BH655 | TRANSF PET WH TOP HT-S8093-BG50WH | +220°C | 500 | FTO |
| BG479 | PET TAG 125 WH TOP HT | +220°C | 500 | FTO |
| BE726 | ALU 60 WHITE TOP-S8093-BG50WH | +375°C | 125 | Ready Width* |
| BE776 | ALU TAG 175 WHITE TOP | +500°C | 100 | Ready Width** |

Service is designed for flexibility, with Fasson® Ready Width™ service options and reduced Minimum Order Quantities.

* 250mm*500lm

** 250mm*100lm*4 rolls



DISCLAIMER - All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2017 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

2017-03_15152EN



Label and Packaging Materials

North Asia

5th Floor, Hongye Park
1801 Hongmei Road,
Xuhui District 200233,
Shanghai, China
+86 21 33951888

South Asia Pacific and Sub-Saharan Africa

460 Alexandra Road
#28-02/03
Singapore 119963
+65 6430 7000

Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 85 000 2000

Latin America

Rodovia Vinhedo-
Viracopos, KM 77
CEP 13280-000
Vinhedo - SP, Brazil
+55 19 3876-7600

North America

8080 Norton Pkwy
Mentor, OH 44060
800.944.8511