

Digital Printing Portfolio

Epson Water-based Inkjet

Fasson® product constructions shown have been evaluated by Avery Dennison and Epson and are recommended based upon the existing printer ink system utilized at the time of testing. Additional product constructions are available.





specialized finishes, are available through the EXACT™ and Ready Width™ service programs. The one-slit roll minimum and next-day shipment are a great complement to the short run/quick turn capabilities of digital presses. Please contact your Avery Dennison sales representative for assistance.

Spec#	Facestock	Adhesive	Liner	Width/Length (In./Ft.)	TMC3400	TMC3500	C831	C-7500	C-7500G
PRIME	PAPER								
53109	DemandJet™ 500HG	AT20	40#SCK	EXACT™/2500	•	•	•	•	
53110	DemandJet [™] 500HG	S2501	40#SCK	EXACT™/2500	•	•	•	•	•
				EXACT™/5000	•		•		
53684	DemandJet™ 500HG	R195	40#SCK	Custom Coat 60/4200	•	•			
53966	DemandJet [™] 500HG FasCover [™]	S2501	40#SCK	Stock 60/1668	•	•	•		•
54197	DemandJet™ SG WBIJ	AT20	40#SCK	Stock 78/1668		•	•		
54166	DemandJet™ SG WBIJ	S2501	40#LF	EXACT™/2500	•	•	•	•	•
53708	Premium Matte WBIJ	S2501	41#LF	EXACT™/2500	•	•	•	•	
54049	Premium Matte WBIJ	AT20	40#SCK	Stock 78/1668	•	•	•	•	•
54058	Premium Matte WBIJ	S246	40#SCK	Stock 60/1668	•	•	•	•	
54060	Standard Matte WBIJ	S2501	40#SCK	EXACT™/2500	•	•	•	•	•
PRIME	FILM								
79659	Gloss White BOPP WBIJ	S7000	40#BG	EXACT™/2500	•	•	•	•	•
79799	Matte White BOPP WBIJ	AT20	40#BG	Stock 60/1668	•	•	•	•	•
79800	Satin White BOPP WBIJ	AT20	40#BG	Stock 60/1668	•	•	•	•	
79668	Gloss Clear BOPP WBIJ	S7000	40#BG	Stock 60/1668	•	•	•	•	•
DURAB	LE FILM								
79348	5 Mil Matte White Drum Label	S4600	50#SCK	EXACT™/2500	•*	•*	•*	•	•
79404	3 Mil Matte White Synthetic	S8001	50#SCK	EXACT™/2500	•	•	•	•	•
79119	2 Mil White WBIJ PET	S8001	50#SCK	Stock 54/1668	•	•	•	•	•
79330	3.2 Mil White WBIJ Vinyl	S730	50#SCK	Stock 54/1668	•	•	•	•	•
79673	5 Mil Matte WBIJ	S8001	50#SCK	Custom Coat 60/4100	**		•	**	•

Recommended: Indicates these substrates meet Avery Dennison proprietary print testing standards. To earn our
recommendation, a specification must have average or better print quality, readability, image traits and durability.

©2017 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, product names and codes are trademarks of Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. Personal and company names and other information on samples depicted are fictitious. Any resemblance to actual names and addresses is purely coincidental.

ADV# 426, 16120, 12/2017, PDF label.averydennison.com

Indicates substrates meet Avery Dennison print testing standards but may require further customer-specific testing in order to confirm their appropriateness for an application.

Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.

NOTE: As label graphics and performance requirements vary, we encourage end use application testing of all materials prior to use.

^{*}Approved for BS 5609 Section 3 when printed with Epson Durabrite™ Inks. ** Approved for UL® 969 Dry Indoor applications when printed using Epson Durabrite™ Inks.